

## In-Wall Access Point

## **GWN7624**

The GWN7624 is an in-wall Wi-Fi access point designed for small-to-medium sized businesses, offices, residential and commercial locations, hotels and more. It provides three Gigabit network ports to provide IP phones, IPTV, computers and similar devices with Ethernet while also providing and uplink Gigabit network port with PoE/PoE+. The GWN7624 offers 2.4G 2×2:2 MIMO, 5G 4×4:4 MU-MIMO technology and a sophisticated antenna design for maximum network throughput and expanded Wi-Fi coverage range. This access point is designed to be mounted in-wall to provide a clean and professional installation that blends into the surrounding environment. To ensure easy installation and management, the GWN7624 uses a controller-less distributed network management design in which the controller is embedded within the product's web user interface. The GWN7624 is also supported by GDMS Networking and GWN Manager, Grandstream's free cloud and on-premise Wi-Fi management platform. It is the ideal Wi-Fi AP for voice-over-Wi-Fi deployments and offers a seamless connection with Grandstream's Wi-Fi capable IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals and 200 concurrent clients per AP, the GWN7624 is an ideal Wi-Fi access point for medium wireless network deployments with medium user density.



2.03 Gbps wireless throughput and 4x Gigabit wireline ports



5GHz 4×4:4 MU-MIMO



Supports up to 200 concurrent Wi-Fi client devices



Advanced QoS to ensure real-time performance of low-latency applications



Anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate/random default password per device



Self power adaptation upon auto detection of PoE or PoE+



Embedded controller manages up to 30 local GWN APs; GDMS Networking offers unlimited AP management, & GWN Manager offers on-premise software AP management

Wi-Fi Standards IEEE 802.11 a/b/g/n/ac Two 5G & two double frequency internal antennas Antennas 2.4GHz, gain 3dBi; 5GHz, gain 5dBi IEEE 802.11ac: 6.5 Mbps to 1733 Mbps IEEE 802.11n: 6.5 Mbps to 600 Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps **Wi-Fi Data Rates** IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps \*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network 2.4GHz Radio: 2412 - 2484 MHz Frequency Bands 5GHz Radio: 5180 - 5825 MHz \*Not all frequency bands can be used in all regions 2.4G: 20 and 40 MHz **Channel Bandwidth** 5G: 20, 40 and 80 MHz WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical Wi-Fi and System Security data/control lockdown via digital signatures, unique security certificate and random default password per device 2×2:2 2.4GHz(MIMO) **MIMO** 4×4:4 5GHz(MU-MIMO) Up to 100 meters **Coverage Range** \*coverage range can vary based on environment 2.4G: 21dBm **Maximum TX Power** 5G: 23dBm \*Maximum power varies by country, frequency band and MCS rate 802.11a: -92dBm @6Mbps, -74dBm @54Mbps; 802.11n 20MHz: -74dBm @MCS7; 802.11n 40MHz:-71dBm @MCS7 802.11ac 20MHz: -67dBm@MCS8; 802.11ac: HT40:- 63dBm @MCS9; 802.11ac 80MHz: -59dBm @MCS9 **Receiver Sensitivity** 2.4G 802.11b: -96dBm@1Mbps, -88dBm@11Mbps; 802.11g: -93dBm @6Mbps, -75dBm@54Mbps; 802.11n 20MHz: -73dBm @MCS7; 802.11n 40MHz:-70dBm @MCS7 SSIDs 16 SSIDs total, 8 per radio (2.4GHz & 5GHz) **Concurrent Clients** Up to 200 1x 10/100/1000M uplink Ethernet port with PoE/PoE+ **Network Interfaces** 2x 10/100/1000M Ethernet port with PSE 1x 10/100/1000M Ethernet port Auxiliary Ports 1x Reset Pinhole **Mounting** In-wall mountable **LEDs** 1 tri-color LED for device tracking and status indication **Network Protocols** IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM QoS 802.11e/WMM, VLAN, TOS Embedded controller can manage up to 30 local GWN APs **Network Management** GDMS Networking offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs Support 802.3az **Power and Green Energy** PoE 802.3af/ 802.3at; Efficiency PSE Maximum Output Per Port: 6W; Maximum Power Consumption: 25W Operation: -10°C to 50°C **Environmental** Storage: -30°C to 60°C Humidity: 5% to 95% Non-condensing Unit Dimension: 135mm(L)x86mm(W)x38.5mm(H) Entire Package Dimension: 176mm(L)x118.5mm(W)x65mm(H) Package Content GWN7624 In-Wall Wireless AP, 4x Screws(KB 3.5\*26), Quick Installation Guide Compliance FCC, CE, RCM, IC, UKCA